

Fully Rugged Tablet PC

RS10A

Tough Features

Drop Resistance	26 drops of 36 inches height to 0.7" plywood over concrete with unit off Mil Std 810G-516.6, Procedure IV
Spill Resistance	Meets Mil Std 810G-506.5, Procedure II, (Unit is not operating IPX5)
Shock Resistance	Mil Std 810G-514.6, Procedure I Cat. 24, Fig.514.6 E-1 & 514.6E-2 (unit is non operating) ASTM 4169-99 Truck Assurance Level II, Schedule E (Unit is operating)
Dust Resistance	Meet IEC 60529 IP-6X standard, No ingress of dust : complete protection against contact

System Specifications

Processor	Intel® Atom N270 1.6GHz Processor
System Memory	200-pin DDRII SODIMM Socket x 1, up to 2GB (Factory Option)
Storage	2.5" SATA Hard Disk/SSD
Display	10.2" WSVGA (1024 x 600) TFT LCD display w/ LED-backlight, Touch Screen panel (AOT) Sunlight readable 500 nit
Chipset	Intel® 945GSE & Intel® ICH7M
Expansion Slot	PCMCIA, Two Mini Card Slot(internal), CompactFlash Slot
Operating system	Windows 7, Vista, XP, Embedded Standard 2009
I/O Ports	<ul style="list-style-type: none"> • One RS-232 • Two USB 2.0 • One Mini USB • One Docking port (contact pin with USB/RS-232/VGA/Power signal) • DC-In jack • Two Audio in/out jack for Microphone/ Earphone • One RJ-45 jack for 10/100/1000Mbps Ethernet • One 15 pin D-sub VGA port for ext. monitor/projector
Audio	<ul style="list-style-type: none"> • High Definition Audio • Internal speaker • Internal Microphone
Wireless/Communications	<ul style="list-style-type: none"> • Gigabit Ethernet(10/100/1000Mbps) • WLAN 802.11 b/g • Bluetooth 2.0 EDR Class 1 Module
Power Supply	<ul style="list-style-type: none"> • AC Power input: 100V-240V, 50Hz-60Hz, 65W • DC Power output: 19V • 3S1P 3cells Smart Li-Ion (4,100 mAh), 3.5Hrs Battery Life
Temperature	<ul style="list-style-type: none"> • Operating Temperature: -4°F ~ 140°F (-20°C ~ 60°C) with HDD heater • Storage Temperature: -67°F ~ 167°F (-55°C ~ 75°C)
Humidity	10 to 95% @ 104°F(40°C), non-condensing
Security	TPM1.2
Dimensions & Weight	270mm(W) x 184mm(D) x 38mm(H) / 10.63"(W) x 7.24"(D) x 1.49"(H) Approximately 1.8Kg / 3.97lbs
Certification	CE / FCC Class B / UL
Green Tech	EPEAT Silver, RoHS Compliance

Docking Station(Optional)

Mounting Interface	Wall mount VESA 75 & 100 compatible
I/O	<ul style="list-style-type: none"> • Four USB 2.0 • One RJ-45 jack for 10/100Mbps Ethernet • One 9 pin D-sub Serial port • One 15 pin D-sub VGA port
Green Tech	EPEAT Bronze, RoHS Compliance

- The specification and pictures are subject to change without notice.
- All brand names are registered trademarks of their respective owners.
- Battery life may vary based on setting and usage.



DURABOOK

GAMMATECH COMPUTER CORPORATION
 Email: sales@gammatechusa.com
 Tel : 1-510-492-0828
<http://www.gammatechusa.com>